



Fig. J1-2. Chassis frame dimensions, 88

AA—Datum line	S—4½ in.	(121 mm)
BB—Front datum	T—1½ in.	(29 mm)
WW—Centre line of front axle	U—3½ in.	(83 mm)
CC—Centre line of rear axle	V—17 in.	(432 mm)
D—134½ in. (3.42 m)	W—15½ in.	(387 mm)
E—21½ in. (540 mm)	X—31 in.	(787 mm)
F—24 in. (610 mm)	DD—60½ in.	(1,53 m)
G—28 ⅝ in. (713 mm)	EE—21½ in.	(540 mm)
H—88 in. (2,235 mm)	FF—24 in.*	(610 mm)
J—29½ in. (743 mm)	GG—10½ in. ± ⅛ in.	(257 mm ± 0.8 mm)
K—14½ in. (375 mm)	HH—10 in. ± ⅛ in.	(254 mm ± 0.8 mm)
L—20 in. (508 mm)	JJ—32½ in. ± ⅛ in.	(835 mm ± 0.8 mm)
M—20 ⅝ in. (523 mm)	KK—11.406 in.**	(290 mm)
N—9 in. (229 mm)	LL—6 ⅝ in.	(167 mm)
P—8½ in. (213 mm)	MM—8 in.	(203 mm)
Q—11 ⅞ in. (297 mm)	NN—28½ in.	(718 mm)
R—7 ⅞ in. (182 mm)	PP—13 ⅞ in. ± ⅛ in.	(332 mm ± 0.5 mm)

\*23½ in. (603 mm)  
 \*\*11 ⅞ in. ± ⅛ in. (294 mm ± 0.8 mm)

} Early  
 } models

880mm door opening width