

DEFENDER TYRE CHARACTERISTICS

TYRE	SIZE	APPLICABLE MODEL	COMMENTS
Michelin XM & S 8 Ply Rating	205 x 16 Radial	Standard fit 90 and V8 models Optional others	Dual purpose, good traction: snow, mud, adverse conditions, low rolling resistance improves M.P.G.
Avon Rangemaster 6 Ply Rating	750 x 16 Radial	Option 110 all models Option 90 2.5 Litre models	Dual purpose, good traction on and off road. Low rolling resistance improves M.P.G.
Michelin XC Type L 8 Ply Rating	750 x 16 Radial	Optional all models	Recommended for all off-road conditions, self cleaning. Resistance to accidental damage.
Michelin XS 6 Ply Rating	750 x 16 Radial	Optional all models	Ideal for sand or similar conditions, maximum flotation heavy loads at reduced pressures, reasonable on-road life.
Michelin X Type 4 x 4 8 Ply Rating	750 x 16 Radial	Optional all models	Dual purpose, good on-road life excellent traction off-road, pro- tector ply in sidewall for off-road.
Michelin XZY 12 Ply rating	750 x 16 Radial	Optional all models	General purpose tyre. Good wear characteristics. Designed to run at low pressures if necessary. Resistance to sidewall intrusion.